



Push-Pull Cable Part Number Codes



SERIES

- 3 = 30 Series
- 4 = 40 Series
- 6 = 60 Series

CORETYPE

- 4 = 1 x 19 armor core: **30 Series**
 - .093 dia. for use with all **30 Series** conduit types
 - High flexibility and moderate efficiency with low lost motion and moderate load applications
- 6 = 1 x 19 armor core: **40 Series**
 - .125 dia. for use with all **40 Series** conduit types
 - High flexibility and moderate efficiency with low lost motion and moderate load applications
- 8 = 1 x 19 armor core: **60 Series**
 - .187 dia. for use with all **60 Series** conduit types
 - High flexibility and moderate efficiency with low lost motion and moderate load applications

PACKAGING

- I = Individual

OVER ALL LENGTH
In inches (Place 0 in first position if less than 100")

PRODUCT OPTIONS
DASH = Standard

TERMINAL MATERIALS

- 4 = S.S. Rod & Conduit Fittings w/Plated Brass Tube

CONDUIT FITTINGS

- BB = Bulkhead type both ends
- GG = Grooved type both ends
- BG = Bulkhead one end, Grooved other end
- C2 = Extension boot for Bulkhead type, 40 & 60 Series
- H2 = Extension boot for Grooved type, 40 & 60 Series

TRAVEL IN INCHES

- 1 = 1" Travel
- 2 = 2" Travel
- 3 = 3" Travel
- 4 = 4" Travel
- 5 = 5" Travel
- 6 = 6" Travel

CONDUIT TYPE

- 0 = Standard construction available in 30, 40 and 60 series and all 30, 40, 60 and 80 series binder wrap conduits
 - Standard construction implies polyethylene liner and black polyethylene covering (-65°F to +225°F)

ASK FOR QUANTITY DISCOUNT Prices subject to change without notice.

BAUM HYDRAULICS CORPORATION

1-800-228-9222 / e-mail: sales@baumhydraulics.com
Fax: 1-800-832-2522 / www.baumhydraulics.com / © Baum Hydraulics Corporation